

SAFETY DATA SHEET

1. Identification

Product identifier	AES-500 Stainless Steel Cleaner	
Other means of identification		
Product code	1000006682	
Recommended use	Cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	INO SOLUTIONS	
Address	9900 Boulevard du Golf Anjou, Quebec H1J 2Y7 Canada	
Telephone	1-888-466-7658	
E-mail	Not available.	
Emergency phone number	Emergency - US	1-866-836-8855
	Emergency - Outside US	1-952-852-4646
Supplier	Not available.	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1

Label elements



Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.	
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2
Other hazards	Combustible.	

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	30 - 60
Acetone		67-64-1	10 - 30
Propane		74-98-6	10 - 30
Methyl Acetate		79-20-9	7 - 13
Citral		5392-40-5	0.1 - 1
Naphtha (petroleum), Heavy Alkylate		64741-65-7	0.1 - 1
Orange Terpenes		68647-72-3	0.1 - 1
Other components below reportable levels			15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe the fumes.
General fire hazards	Extremely flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	Inhalable fraction and vapor.
	TWA	250 ppm	
Citral (CAS 5392-40-5)	TWA	5 ppm	
	STEL	250 ppm	
Methyl Acetate (CAS 79-20-9)	TWA	200 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm
	TWA	1200 mg/m3 500 ppm
Methyl Acetate (CAS 79-20-9)	STEL	757 mg/m3 250 ppm
	TWA	606 mg/m3 200 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	Non-aerosol.
	TWA	250 ppm	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	
	STEL	250 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
	TWA	200 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapor.
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3
		1000 ppm
	TWA	1190 mg/m3
		500 ppm
Methyl Acetate (CAS 79-20-9)	STEL	757 mg/m3
		250 ppm
	TWA	606 mg/m3
		200 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	109.56 °F (43.09 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.7 % estimated
Flammability limit - upper (%)	13.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	665.75 °F (352.09 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.515 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact May cause an allergic skin reaction.
Eye contact Causes serious eye irritation.
Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause an allergic skin reaction.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Citral (CAS 5392-40-5)		
Acute		
Dermal		
LD50	Rabbit	2250 mg/kg
	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Mouse	1424 mg/kg
	Rat	4895 mg/kg
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg > 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Methyl Acetate (CAS 79-20-9)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC100	Rabbit	98.4 mg/l, 4 Hours
Oral		
LD50	Rat	6482 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
ACGIH sensitization	
Citral (CAS 5392-40-5)	Dermal sensitization
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
ACGIH Carcinogens	
Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.
Citral (CAS 5392-40-5)	A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: carcinogenicity	
ACETONE (CAS 67-64-1)	Not classifiable as a human carcinogen.
CITRAL, INHALABLE FRACTION AND VAPOR (CAS 5392-40-5)	Not classifiable as a human carcinogen.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)

Components	Species	Test Results
Citral (CAS 5392-40-5)		
Aquatic		
Algae	IC50	Algae 16 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7 mg/L, 48 Hours
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.9 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)		
Aquatic		
Algae	IC50	Algae 120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas) 295 - 348 mg/l, 96 hours
Naphtha (petroleum), Heavy Alkylate (CAS 64741-65-7)		
Aquatic		
Algae	IC50	Algae 30000 mg/L, 72 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Methyl Acetate	0.18
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable

Transport hazard class(es)**Class** 2.1**Subsidiary risk** -**Label(s)** 2.1**Packing group** Not applicable.**Environmental hazards** No.**ERG Code** 10L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed with restrictions.**Cargo aircraft only** Allowed with restrictions.**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS**Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Label(s)** 2.1**Packing group** Not applicable.**Environmental hazards****Marine pollutant** No.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.**IATA; IMDG; TDG****15. Regulatory information****Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Acetone (CAS 67-64-1)

Class B

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 09-17-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names